



## KINGFISHER K-X10

### DESCRIPTION.

**Kingfisher K-X10** is formulated as a solvent based decorative wood treatment which provides excellent protection against timber decay, fungal attack, and rainwater penetration.

It is resistant to ultra-violet deterioration and is permeable to water vapour, which allows the timber substrate to breathe

These features ensure protection against deterioration and decay and consequently significantly reduces maintenance costs.

**Kingfisher K-X10** provides a semi-transparent finish which allows the natural grain of the timber to be visible after application. It provides a semi-gloss finish and is ideal for use on doors, window joinery, sheds, gates, fencing, cladding, fascias, garden furniture etc. where a natural finish is desired.

**Kingfisher K-X10** is available in 5 litre containers in a choice of Mahogany, Pine or Walnut.

### METHOD of USE.

**Kingfisher K-X10** is normally applied by brush. The surface to be treated should be clean, dry and free from oil, grease, mould, dirt paint or varnish. For external joinery, added protection can be provided by coating with **Kingfisher Clear Preservative** prior to decorative treatment with **K-X10**. Allow preservative to dry for approximately 24 hrs. prior to **K-X10** application.

The moisture content of the timber should be less than 21% at the time of treatment.

Apply **Kingfisher K-X10** by brush to provide an even coat. Where the product has been subject to storage, stir before use.

Allow the first coat to dry thoroughly for 24 hours before a second coat or other finish is applied.

Brushes and other equipment should be cleaned with **Kingfisher Turps** or White Spirit after use.

### COVERAGE.

**Kingfisher K-X10** will cover approximately 4 – 8 sq metres per litre depending on the porosity of surface being treated.

### MAINTENANCE.

Clean down timber with a stiff brush to remove all dirt and loose material. Where holes and other imperfections are to be repaired use **Kingfisher Woodfiller**.

For best results, mix with a portion of **K-X10** prior to application to provide a complete match

### TECHNICAL DATA.

Shelf Life - 2 Years (Unopened Containers.)  
 Drying Time. - 4 – 8 Hours (Allow 24 hours between coats.)  
 Product is Flammable.

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept Tel. 01229 869100 or Fax 01229 869101.  
[www.kingfisheruk.com](http://www.kingfisheruk.com)

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USERS RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.